


OUTILS FORANTS DRILLING BITS



NORMALISATION STANDARDS

Diam. Ext. O.D.		Diamètre Intérieur I.D. +0 -0.25								
+0.25	+0	B	D	T2	CLT2	T6	CLT6	T6S	TT	K
36	22.00			22.00						
46	32.00			32.00					35.50	
56	42.00			42.00					45.50	
66	52.00			52.00	48	47.00	43	38.00		38.00
76	62.00		56.00	62.00	58	57.00	53	48.00		48.00
86	72.00		66.00	72.00	68	67.00	63	58.00		58.00
101	87.00		81.00	84.00	80	79.00	76	72.00		72.00
116	102.00		96.00			93.00	90	86.00		86.00
131	117.00		110.00			108.00	103.5	100.80		101.00
146	132.00		122.00			123.00	118	115.80		116.00

Diam. Ext. O.D.		Diamètre Intérieur I.D. +0 -0.25					
+0.25	+0	P	M	CHD	GWSK	NSK	GBS/SK6L
76				43.60			
78						47.50	
93	77.00		66.00				
94					57.00		
95						57.00	
101				63.50			
112	95.00		85.00				
122						79.00	
124					78.60		
132	114.00		101.00				
134				85.10			
146						102.00	102.00
158					101.60		
176						132.00	

Diam. Ext. O.D.		Diamètre Intérieur I.D. +0 -0.25				
+0.25	+0	WF COURT / SHORT	WG	WM	WT	T-W
R	29.34				18.80	
E	37.21	21.59	21.59	21.59	23.11	
A	47.50	30.23	30.23	30.23	32.66	33.05
B	59.44	42.16	42.16	42.16	44.58	44.75
N	75.18	54.86	54.86	54.86	58.88	60.50
H	98.60	76.33	76.33		81.08	
P	116.76	92.33				
S	145.16	122.95				
U	173.36	140.08				
Z	198.76	165.48				

Diam. Ext. O.D.		Diamètre Intérieur I.D. +0 -0.25	
+0.25	+0	WL	WL3
AWL	47.50	27.09	
BWL	59.44	36.52	33.65
NWL	75.18	47.74	45.21
HWL	95.50	63.62	61.23
PWL	121.80	85.09	83.18

Diam. Ext. O.D.		Diamètre Intérieur I.D. +0 -0.25	
+0.25	+0	WF LONG	
HWF	98.98	76.33	
PWF	120.40	92.33	
SWF	145.80	122.95	
UWF	174.24	140.08	
ZWF	199.64	165.48	
412F	106.95	74.72	

Diam. Ext. O.D.		Diamètre Intérieur I.D. +0 -0.25	
+0.25	+0		
AMLC	47.60	27.00	
BMLC	59.60	35.20	
NMLC	75.30	51.20	
HMLC	98.40	63.50	

Diam. Ext. O.D.		Diamètre Intérieur I.D. +0 -0.25	
+0.25	+0		
AXT	47.60	32.50	
BX	59.60	42.00	
NX	75.18	54.86	
HX	98.60	76.33	